

Assembly instructions for Telephone-Connection Box A/N (TG) to the Intercom

To operate a cell phone, a suitable hands-free phone system is necessary. Furthermore, the hands-free phone system has to have a mute outlet (normally this will be used to mute the radio)

The Junction- box and the hands-free phone system will be installed underneath the front left storage compartment.

Make the connections of the operating voltage as described in the wiring plan. In most cases the set of cables from the hands-free phone system can be used.

Connect the 3 single cables coming from the Connection Box with the wires of the hands-free system. Black = ground, Red = 12 V pole of the ignition lock, Blue = mute outlet of cell phone.

Connect the 2 jack plugs MIC and SPEAKER TEL. With the hands-free phone system. As soon as all connections are made, the installation is ready to be used.

On the back of the Connection Box there are 2 regulation buttons. The button "MIC" adjusts the speaking volume, button "Spk.Tel." adjusts the listening volume of the cell phone. On delivery, both buttons are turned to their maximum.

To test the installation, connect the cell phone with the hands-free unit.

Connect the helmet, and start the ignition. Call your own cell phone.

If all connections are made correctly, you should be able to hear the ringing of your phone in an acceptable volume within your helmet. Answer the phone and check the audibility.

The microphone within the helmet shouldn't be turned to a too sensitive position because there might be too much interference while driving. **With a distance of only 10 cm of the microphone audibility should be impossible! To reduce the sensitivity of the microphone use the regulation button "Mic." on the back of the Connection Box. The sensitivity should be reduced for a good audibility to be possible with a close distance (2-5 cm) only.**

With correct adjustments, audibility is secured for an open jet-helmet to speeds up to app. 100 km/h in a nice quality, and for an integral-helmet to speeds up to app. 160 km/h.

If everything works correctly, protect the junction box and the hands-free unit with a plastic bag and fasten it with a cable fixer. Fasten the junction Box carefully under the storage compartment (if needed use 2-sided adhesive tape).

Assemble all de-installed parts.

In case of occurring problems, please do not hesitate to contact us at +49(0) 4122 967690. We help you.



Klinkerstrasse 7, 25436 Moorrege, Germany
Phone 0049 4122 967690, Fax 0049 4122 967689
Mail irlbacher@w-irlbacher.de, www.w-irlbacher.de

